

6-Button Massio™ Keypad (US, UK and Europe)

MKP-106P-BL (FG5793-06P-BL), Portrait, Black MKP-106P-WH (FG5793-06P-W), Portrait, White MKP-106L-BL (FG5793-06L-BL), Landscape, Black MKP-106L-WH (FG5793-06L-W), Landscape, White



Overview

The MKP-106 / 6-Button Massio Keypad is a keypad-only version of the MKP-106 Massio ControlPad. The MKP-106 provides sleek Massio styling in any room, serving as a second user interface or as a primary UI in spaces that already contain a separate controller. The MKP-106 includes large, easy-to-read buttons in a stylish design that makes it simple for users to manage complex tasks with a single button press during meetings or classes. The Keypad connects to the controller via Ethernet, which simplifies installation and connectivity.

Common Applications

- Ideal for small spaces utilizing NetLinx control, providing the ability to utilize customized code and additional ports of NetLinx masters, while maintaining a consistent user experience as the RPM-enabled Massic ControlPads.
- Perfect for Massio rooms requiring a second user interface in the same form factor to act as a slave keypad to the Massio ControlPad."

Features

Consistent Massio Aesthetics & Form Factor - Provides consistent look-and-feel in existing installations
with Massio, with the same models and sizes as the Massio ControlPads

- Massio Styling in Customized Rooms Provides Massio-style UI in rooms that require a separate controller
- Connects Via Standard Protocols (PoE) Simplifies cabling and installation by minimizing cable runs and eliminates the need for power at the keypad location

Specifications

GENERAL	
Dimensions (HWD)	Portrait: 4 11/16" x 3 7/16" x 9/16" (119 mm x 87.5 mm x 13.9 mm) Landscape: 3 7/16" x 4 11/16" x 9/16" (87.5 mm x 11 mm x 13.9 mm) Mount onto standard 1 gang US, UK, or EU back boxe
Weight	Approximately .25 lbs (.11 kg)
Front Panel Components	6 Buttons
Color / Styles Available	Portrait, Black: MKP-106P-BL (FG1313-06P-B) Portrait, White: MKP-106P-WH (FG1313-06P-W) Landscape, Black: MKP-106L-BL (FG1313-06L-B) Landscape, White: MKP-106L-WH (FG1313-06L-W)
Regulatory Compliance	 FCC CFR Title 47 Part 15 CE EN 55022 CE EN 55024 CE EN 60950-1 IEC 60950-1 UL 60950-1 C-Tick CISPR 22 IC CISPR 22 VCCI CISPR 22 ROHS WEEE

	ACTIVE POWER REQUIREMENTS	
Γ	Voltage, DC (Typical)	DC (Typical): PoE (37V-57V)
	Voltage DC Range	37 V-57 V per 802.3af spec
Ī	Power Connector	(1) RJ-45 Ethernet

POWER SUPPLY	
External, Required	Any POE injector or switch, conforming to the 802.3af standard including AMX's PS-POE-AF-TC (FG423-83), not included

ENVIRONMENTAL	
Temperature (Operating)	32° to 122° F (0° to 50° C)
Temperature (Storage)	14° F to 140° F (-10° C to 60°C)
Humidity (Operating)	5% to 85% RH

ETHERNET	
Ethernet Connection	(1) 10/100; Port provides TCP/IP communication. This is an Auto MDI/MDI-X enabled port, which allows you to use either straight-through or crossover Ethernet cables. The Ethernet Port LEDs show communication

	activity, connection status, speeds, and mode information
CONTROL PORTS & INDICATORS	
Program Port	(1) USB Mini-B, USB
ID Pushbutton	Reset factory settings, reset factory image, toggle between DHCP or static IP addressing mode
MEMORY	
Flash	4 GB
Memory Card	4 GB SD
DDRAM	256 MB

About AMX by HARMAN

Founded in 1982 and acquired by HARMAN in 2014, AMX® is dedicated to providing AV solutions for an IT World. AMX solves the complexity of managing technology with reliable, consistent and scalable systems comprising control, video switching and distribution, digital signage and technology management. AMX systems are deployed worldwide in conference rooms, classrooms, network operation/command centers, homes, hotels, entertainment venues and broadcast facilities, among others. AMX is part of the HARMAN Professional Group, the only total audio, video, lighting, and control vendor in the professional AV market. HARMAN designs, manufactures and markets premier audio, video, infotainment and integrated control solutions for the automotive, consumer and professional markets. Revised 8.31.16. ©2016 Harman. All rights reserved. Specifications subject to change.

www.amx.com | +1.469.624.7400 |800.222.0193